

SPECIFICATION CHART

Model	Load Capacity* (lbs.)	Engine HP/rpm net (SAE-HP)	Maximum Travel Speed (m.p.h.)	Maximum Lift Speed Full Load (f.p.m.)	Maximum Gradeability Full Load (%)	Basic Right Angle Stack** (in.)	Turning Radius (in.)	Overall Truck Dimensions (in.)		
								Length***	Width	Height
8FGU15	3,000	51/2570	11.5	131	45	92.1	76	87.8	42.1	81.9
8FDU15	3,000	53/2400	11.5	128	45	92.1	76	87.8	42.1	81.9
8FGU18	3,500	51/2570	11.5	131	45	94.1	78	89	42.1	81.9
8FDU18	3,500	54/2400	11.8	128	45	94.1	78	89	42.1	81.9
8FGU20	4,000	51/2570	10.9	118	41	103.2	84.7	101.4	45.3	83.1
8FDU20	4,000	54/2400	11.8	121	41	103.2	84.7	101.4	45.3	83.1
8FGU25	5,000	51/2570	10.9	118	34	105.9	87.5	103.9	45.3	83.1
8FDU25	5,000	57/2500	11.8	121	34	105.9	87.5	103.9	45.3	83.1
8FGU30	6,000	51/2570	11.2	100	26	111.4	92.5	110	48.8	85.5
8FDU30	6,000	57/2500	11.8	98	29	111.4	92.5	110	48.8	85.5
8FGU32	6,500	59/2570	11.2	100	26	112.4	93.3	110.9	48.8	85.5
8FDU32	6,500	57/2500	11.8	98	29	112.4	93.3	110.9	48.8	85.5

* Based on 24" load center.

** Add load length and clearance.

*** Length to fork face.